





Spray Nozzle Products for Food Processing Industry





We deliver the perfect fit for your needs.

In the industrial sector, spray nozzles are essential for product manufacturing. They are utilized throughout the manufacturing process for tasks such as cleaning, cooling, humidification, and air blowing, covering a wide range of applications. Additionally, spray nozzles play a crucial role in maintaining hygiene, quality, and safety.

Using the right nozzle for each specific purpose allows you to achieve water and energy savings, promote recycling, reduce costs, and enhance manufacturing efficiency.

To provide the 'perfect fit' spray nozzles that meet our customers' needs, we develop a wide range of products, units, and systems, and collaborate with our customers to tackle challenges from various perspectives.



How to optimize your process

There are various ways to achieve efficient results. One approach is to not only switch spray nozzles but also pursue automation and mechanization.

By delegating manual tasks to spray nozzles and implementing mechanization, you can significantly reduce operational costs.

Automating the previously manual operation of the nozzles and integrating them into units or systems allows for labor reduction and improved efficiency.

Benefit from our extensive technology and experience in designing units and automated systems that utilize our spray nozzles.

If you are considering automation or streamlining processes, please feel free to consult with us.

Tips 01.

 MOVIES

YouTube Channel (packed with 'I see' moments)



Explore the IKEUCHI Channel on YouTube for a variety of videos covering spray nozzles.

Discover insightful content including product demonstrations, usage guides for units and systems, maintenance tips, and insights into humidity and static electricity relationships.

IKEUCHI channel



Tips 02.

 CASE STUDIES

Review Our Case Studies



Dive into real-life examples showcasing the effectiveness of spray nozzles, offering detailed insights beyond what's covered in our catalog. Our team is ready to assist with specific nozzle applications and specifications not listed. The applications and spray nozzles in this catalog are just a few examples. For any not covered, please feel free to reach out to us.


IKEUCHI food case study



Tips 03.

 BASICS

Master the Basics of Nozzles



Spray nozzles can produce various effects depending on how they are used. We will share key tips for effective use of nozzles. Please refer to pages 25–30 and visit our website for more information.

3D/2D CAD models of IKEUCHI's products can be previewed and downloaded for free on the PARTcommunity website.

Feel free to explore this service.

To view some products an account is required. Registration is free of charge.

https://ikeuchi.partcommunity.com/3d-cad-models/?languageIso=en&info=ikeuchi/metric_unit



●Note: Specifications of the products and contents of this catalog are subject to change without prior notice for purpose of product improvement.

CONTENTS

Spray Nozzle Products for Food Processing Industry

Product Applications for Food & Beverage Processing

pp. 5–22



Cleaning and Thermal Sterilization of Tanks	5
Cleaning, Disinfection and Deodorization of Conveyors	7
Cleaning Complex-shaped Objects	9
Air Blowing	11
Humidity Control in Food Processing	13
Moisture and Humidity Control for Packaging	15
Disinfection and Deodorization of Objects and Spaces	17
Cooling and Heat Treatment	19
Water Filtration and Liquid Agitation	21

For Effective Use of Nozzles

pp. 23–28


Spray Nozzle Precision Guarantee Fog Classification System	23
Spray Nozzle Selection	24
Benefits of Switching Nozzles	25
Spray Nozzle Materials	27
How to Read the Catalog Charts	28

Links to Digital Catalogs

Digital catalogs for our products are available on our website. Click on the banner on the right or scan the QR code to access each of our e-catalogs.

<https://we.kinkosonline.jp/apps/home/kirinoikeuchi>

🔍 IKEUCHI digital catalog



Tank Cleaning Nozzle Catalog



RJ Series, RJ3-MD Series, JA Series, ES Series, ES/ESV-PTFE Series, SR Series, SWB Series, RJ2-PON Series, etc.




Hydraulic Spray Nozzle Catalog



VVP / VP Series, UVVP Series, INVV Series, AWWV Series, SO-VV/SO-V Series, SD-VV Series, SD-CC Series, VEP / VE Series, VNP Series, YYP Series, INQB Series, KB Series, KBN Series, JJXP Series, INJJX Series, BBXP Series, AJP Series, 7JJXP Series, CCP / CP Series, 2CCP / 7CCP Series, 2CP / 7CP Series, EJX Series, UT / WUT Joint Adaptors, etc.



Dry Fog Humidifier AKIMist “E”



Pneumatic Spray Nozzle Catalog



BIM Series, CBIM Series, SCBIM Series, SETOJet Series, SETOV Series, SETOV-C Series, YYA Series, etc.



Air Nozzle Catalog



TAIFUJet Series (including TF-F, TF-FS, TF-PF and TF-R Series), CCP-A Series, SLNHA-H Series, EJA Series, etc.



Auto-strainer ARS Filter



Note: Please confirm that any food-contact surfaces of our products comply with the applicable food safety regulations and standards.

Tank Cleaning and Thermal Sterilization

Containers, vessels, and sanitary cans

Trust us with CIP cleaning and HACCP compliance. Automate and optimize your tank cleaning for greater efficiency.

- A wide range of nozzles is available for cleaning tanks of any size, catering to various types of dirt and cleaning methods.
- With high cleaning power and large spray coverage, our nozzles ensure complete cleaning with no spots left unwashed while using less water. They deliver efficient results and achieve significant water savings.
- Automating manual tank cleaning with our nozzles eliminates uneven performance and reduces cleaning time.
- For cleaning large surfaces, our SR and ES Series nozzles, which provide 360° spray coverage, are highly effective.
- For processes prone to residue or stubborn dirt, we recommend nozzles with strong cleaning power, such as the RJ and JA Series.

● Application

Cleaning of conveyors, storage tanks, barrels, sanitary cans, reactor vessels, mixing tanks, and various containers

Note: For CIP applications, please confirm that any wetted surfaces of our products comply with the applicable food safety regulations and standards.



Nozzle automatically moved up and down

Automatic Nozzle Lifting System NLD Series

An automatic lifting device for cleaning tall tanks. Connect a tank cleaning nozzle (ES or SR Series) to the tip of the device, which ascends and descends with a maximum stroke of about 1.7 m. Contact us for more details.

For Hard-to-Remove Dirt

3D Rotation Type: Solid stream jet powerfully cleans the inside of a tank


RJ Series

Low-speed rotation



- Heat-resistant up to 80°C, with custom options for higher resistance.
- Compact design allows for easy installation even if the inlet is small.

JA3 Series



- Two or four solid stream jets powerfully clean the inside of a tank.
- Available for low to medium pressure use.

JA3-D180 Series



- 180° downward spray coverage is ideal to clean inside of open-topped tanks.

For Easy-to-Remove Dirt

2D Rotation Type: Flat spray pattern quickly cleans a large area

SR Series

Low-speed rotation




- Low-speed rotation of 3–15 rpm at 0.3 MPa for effective cleaning.
- Heat resistant up to 150°C.

ES Series



- Unique design ensures hygiene with self-cleaning features.
- Can be mounted in any direction, vertically, horizontally or diagonally.

ES/ESV-PTFE Series



- Highly resistant to chemicals.
- Can be mounted in any direction, vertically, horizontally or diagonally.

Suitable for permanent installation

Pressure-open Nozzle

RJ2-PON Series



- Pressure-activated nozzle with the tip protruding only during spraying and closing flush with the inner wall when not in use.
- Ideal for duct cleaning.

Simple structure

Fixed Type

SWB Series



- Non-rotating shower ball nozzle spraying radially. The simplest design.
- Chemical-resistant PTFE option available.

Watch Our Tank Cleaning Nozzles in Action!



IKEUCHI Channel on YouTube

Cleaning, Disinfection & Deodorization of Conveyors

Nets, conveyors, and filter cloths

Stubborn dirt? Hard-to-clean nets? No challenge! Our efficient, water-saving nozzles make cleaning easy.

- In conveyor cleaning, flat spray nozzles use less water yet deliver the same spray impact as cone spray nozzles, resulting in improved water efficiency.
- Using flat spray nozzles that provide even spray distribution in a multi-nozzle arrangement ensures uniform cleaning, even for wide conveyors.
- In the multi-nozzle arrangement, adjusting the nozzle spacing and spray height facilitates the use of an appropriate number of nozzles, resulting in water savings and cost reductions.
- For disinfecting and deodorizing conveyors, the BIM and KB series cone spray nozzles deliver excellent performance and save liquids by spraying a small volume uniformly over a wide area.
- For clogged nets or stubborn dirt, the VNP series flat spray nozzles for high-pressure cleaning are recommended.

● Application

Cleaning: Conveyors, nets, baking sheets, cases, rolls, and filter cloths.

Disinfection and Deodorization: Conveyors, nets, and food containers.



Foam cleaning: effective for stubborn dirt and odor

Detergent Foam Spray Unit AWA Cart Series

The unit can switch to produce foam with any of three properties: flowing, creamy, or mousse-like.

Replacing the nozzle tip allows for switching the spray pattern between flat and straight types. The spray gun is available either in the standard type or the long-handled lance model.

Contact us for further details.

Cleaning Conveyors

A multi-nozzle arrangement ensuring uniform cleaning even for wide conveyor belts

VVP Series




- Flat spray nozzles with a mountain-shaped spray distribution.
- A multi-nozzle arrangement ensures uniform spray distribution across the entire spray width.

INVV Series




- Flat spray nozzles featuring quick-detachable nozzle tips that reduce maintenance time.
- Made of highly chemical and heat resistant plastic.



Disinfecting & Deodorizing Conveyors

BIM Series




- Produces fine fogs with a mean droplet diameter of 100 μm or less.
- Clog-resistant design available in a wide variety of models.

KB Series



- Hollow cone spray nozzles capable of producing the finest fog among all hydraulic spray nozzles.
- Features a wear-resistant ceramic orifice.

Fine fogs achieving uniform disinfection, deodorization, and quick drying





Cleaning Nets and Filter Cloths

Cleaning clogged dirt, stubborn dirt

VNP Series



- For high-pressure cleaning of containers, tanks, and filters.
- Features a wear-resistant ceramic orifice.



Cleaning Complex-shaped Objects

Bottles, returnable containers, pallets

No problem with hard-to-clean objects like bottles and cans. Effective cleaning with nozzles suited to the objects.

- For cleaning bottles and cans, solid stream jet nozzles provide powerful spray impact and excellent performance. They effectively eliminate blind spots with a force that reaches the bottom.
- It is also effective to enhance cleaning performance by selecting nozzle types suited to the specific cleaning targets or by using a combination of several types.
- To clean different points after installing the nozzles, we recommend using universal joints, which allow spray direction adjustment by hand and reduce work time.

● Application

Cleaning: Bottles, cups, containers, and food containers.



Quickly adaptable to various objects to be cleaned

Universal Ball Joints UT Series

Allows for precise alignment of the nozzle after installation. Ideal for applications requiring angled installation or frequent spray direction adjustments. The spray direction of the nozzle is adjustable as desired within a range of 50°.

Cleaning Bottles and Cans

Thoroughly cleaning bottles and cans down to the bottom with solid stream jets

CP Series




- Solid stream nozzles that produce straight liquid jets.
- Features a wear-resistant ceramic orifice.

7CP Series



- The nozzles that produce seven solid stream jets.
- Features a wear-resistant ceramic orifice.



Cleaning Returnable Retainers

Nozzles and joints with easy angle adjustment enhancing versatility

INQB Series




- Quick-connect adaptors for easy attachment to pipes, and nozzle tips that are easily attachable.
- Allows for adjusting the spray direction within a range of 50 degrees.

WUT Series



- Universal joints for connecting spray nozzles, enabling a 360-degree spray direction adjustment.



Cleaning Surfaces of Finished Product Packages

VEP Series




- Flat spray nozzles with a uniform spray distribution across the pattern area, featuring a wear-resistant ceramic orifice.

JJXP Series



- Full cone spray nozzles with a round-shaped spray area with uniform distribution.
- A large free passage diameter minimizes clogging.

Combining nozzles with different spray patterns ensuring no narrow spots left uncleaned



Air Blowing

Drying and blowing off


Air blowing is essential in every process. Optimizing your air blowing process can help lower operating costs.

- In general manufacturing facilities, improving the air blowing process, which consumes a significant amount of electricity, can effectively achieve energy savings.
- Simply replacing basic pipes, which have only squeezed outlets, with our nozzles exclusively designed for air blowing can reduce your operating costs.
- Switching from nozzles that use compressed air to those that use blower air can reduce operating costs more effectively.
- Our air nozzle lineup includes various types, each suited for different object sizes or blowing spaces.
- The TAIJUJet series, featuring a low-noise design, improves the noise issues associated with air blowing operations.

● Application

Blowing off water droplets, dirt, and defective products for sorting.

Blow-off drying after washing, detaching workpieces during conveying, and transferring powder.



Long, energy-saving blower air nozzles

TF-BPF Series

Long, flat blower air nozzles designed to uniformly cover wide areas. Lowers energy costs to one-third of those consumed by compressed air nozzles.

The structure, designed to accommodate 42-mm wide nozzle tips arranged in a line, allows for manufacturing the nozzle to any desired length.

Contact us for further details.

Blowing Off Water Droplets

An extensive lineup of air nozzles featuring various air blowing patterns

TAIFUJet

TF-FS Series




- Capable of uniform, high-impact, and powerful air blowing.
- Low noise level.
- Compact size suitable for use in tight spaces.
- A blower air type (TF-BF) is also available.

TAIFUJet

TF-R Series



- Capable of powerful air blowing from eight orifices.
- High-impact and powerful air blowing.
- Low noise level.
- A blower air type (TF-BR) is also available.



Blowing off Defective Products

Blowing off defective products for sorting

TAIFUJet

TF-FS Series




- Capable of uniform, high-impact, and powerful air blowing.
- Low noise level.
- Compact size suitable for use in tight spaces.
- A blower air type (TF-BF) is also available.

CCP-A Series



- Blows a single straight air stream.
- Highly cost-effective.
- Compact size ideal for use in multiple quantities.
- Blowing off water droplets with air knives.



Air Knives


TAIFUJet

TF-PF Series



- Air knives capable of covering a wide area.
- Available air blow widths from 200 mm to 1,200 mm.

SLNHA-H Series




- Blows air in a curtain shape from a slit in the nozzle.
- Designed for air blowing with uniform impact distribution in the width direction.

Powder Transfer

EJA Series



- Air injection and suction volumes are adjustable.
- Effective not only for air blowing but also for powder transfer.



See Our Air Nozzles in Action!

Humidity Control in Food Processing

Dough, noodles, cheese / Fermentation rooms and storage

Environmental control always comes first in food storage facilities.

Appropriate humidity control maintains high quality and reduces defect rates.

- Humidity control prevents quality deterioration due to insufficient humidity and minimizes production volume decreases due to dryness.
- Humidity can be controlled in a manner suited for each purpose, from humidifying the entire room to specific areas or production lines where needed.
- For example, mounting multiple pneumatic nozzles that can spray a small volume onto a header enables moisture conditioning of products on a production line only.
- When humidifying a large space, we recommend using the humidity control function. This ensures optimal humidity levels and creates a stable environment.
- When humidifying or moisture conditioning local spots only, using adaptors that can adjust spray directions is an effective approach.

● Application

Moisture conditioning of dough, and humidification in fermentation rooms, storage facilities, and aging rooms for liquor such as wine.

Humidity control in mushroom cultivation rooms.



Angle-adjustable

AE-UT Adaptor

Universal adaptors for the Dry Fog Humidifier AKIMist "E", enabling adjustment of its spray direction horizontally or vertically as desired. They can be used for applications where spraying is desired in the upward or downward direction, or when intensive spraying from multiple nozzles in the same direction is needed.

Humidification in Fermentation Rooms


Precise humidity control with Dry Fog

AKIMist "E"

AE Series



- Produces ultra-fine fog with a mean droplet diameter of 10 μm or less.
- Non-wetting Dry Fog reaches over four meters horizontally, effectively covering a large space.



Humidification in Cold Storage Warehouses

During the curing treatment

AKIMist "E"

AE Series



Humidity Control in Mushroom Cultivation

For drip-free humidity control

AKIMist "E"

AE Series



Moisture and Humidity Control for Packaging

Labels, films, packages, and product bagging

Damage caused by static electricity and dryness cannot be ignored.

For improved product yield and stable operations, humidity control is essential.

- Defects in the final production line can be minimized by addressing static electricity and dryness. Humidity control is one of the key measures.
- For comprehensive humidity management, we recommend implementing a humidity control system, while nozzles and humidification units are effective solutions for localized humidity control.
- Just slightly moistening labels and stickers before attaching them prevents defects in the final products caused by cracking, thereby increasing yield rates.
- Localized humidification close to the production line is also an effective solution for preventing bagging failures caused by products and bags sticking together due to static charge.
- Maintaining an appropriate humidity level prevents static electricity, reduces double-feeding of packaging films in the packing process, and ensures stable operations.

● Application

Moisture conditioning for packaging, labels, and stickers.
Humidification in packing and film feeding processes.



Portable humidifier unit

AE-T Set

A portable humidifier unit, integrating a humidifier (AKIMist "E"), a water pressure tank, and a stand, requires no plumbing work. Simply place it anywhere and just supply compressed air to start its operation.

Equipped with caster wheels, this unit can be easily moved and installed wherever needed within a factory.


Moistening Label Stickers

Slightly moistening labels with spray nozzles prevents label cracking and promotes adhesion to products

BIM Series



- Produces fine fogs with a mean droplet diameter of 100 μm or less.
- Clog-resistant design available in a wide variety of models.



Preventing Static Electricity in Packaging

AKIMist "E"


AE Series




- Produces ultra-fine fog with a mean droplet diameter of 10 μm or less.
- Non-wetting Dry Fog reaches over four meters horizontally, effectively covering a large space.

Dry Fog enables precise humidity control and prevents in-process failures caused by static electricity.

Prevents powder adhesion and bagging failures due to static charge on powder or bags



Prevents film sheets from sticking together and avoids double-feeding failures due to static charge



Disinfection & Deodorization of Objects & Spaces

Bottles, cans, returnable containers, pallets & factory spaces


Sanitation management is crucial in food processing. It is vital not only to keep everything clean but also to make the work environment even cleaner.

- Maintaining cleanliness at processing sites is essential for ensuring production output and high yield rates. Deodorizing and disinfecting these spaces are effective measures.
- Disinfecting the spaces helps maintain good sanitation in compartments and rooms, and integrating with the control system ensures that the environment remains at optimal levels.
- Disinfecting inside the ducts is also an effective solution for keeping the air at worksites clean. The BIM series performs efficient disinfection while conserving disinfectant.
- For localized disinfection on a production line, the BIM series, which can apply alcohol or disinfectant in a fine fog, delivers effective performance.
- Pasteurization requires a large volume of water. For water conservation, the full cone spray nozzle AJP series, which can spray over a wide area, is ideal.

● Application

Disinfection and deodorization of containers, bottles, cans, and products before packing.

Disinfection and deodorization in entrances and exits, within factories, inside ducts, and in cooling rooms.



DIY humidifier unit

AE-KIT


A DIY kit, comprising a spray unit, a control unit, a water unit, a filter unit, and a piping unit, can be easily wall-mounted and operated.

It is capable of humidifying an area of up to 800 m³.

Pasteurization of Containers

Automatic spraying is possible with sensors

AJP Series



- The design without a whirler allows for a large free passage diameter, making the nozzle clog-resistant.
- Features a tangential design with the spraying axis at a 90-degree angle from the nozzle inlet.


Disinfection & Deodorization in Ducts and Cooling Rooms

Fine fog spray ensures thorough disinfection and deodorization

BIM Series



- Produces fine fogs with a mean droplet diameter of 100 μm or less.
- Clog-resistant design available in a wide variety of models.




Disinfecting and Deodorizing Spaces

AKIMist "E"

AE Series



- Produces ultra-fine fog with a mean droplet diameter of 10 μm or less.
- Non-wetting Dry Fog reaches over four meters horizontally, effectively covering a large space.



A chemical-resistant type, AE-TN Series is available, featuring titanium material for the parts that come into contact with chemical liquids.

Cooling and Heat Treatment

Cooling after heat treatment and defrosting

Uniform cooling and defrosting are crucial for product quality.


Achieve an even and effective spray with our nozzles.

- When cooling heat-sterilized products, the nozzle effectively cools each layer of products arranged on shelves.
- When frost forms in a freezer, it can reduce freezing efficiency and increase electricity costs. The nozzle evenly sprays warm water to defrost.
- To efficiently cool or defrost the interiors of shelf-like and large compartments, we recommend using a nozzle header with multiple nozzles arranged along the piping.

● Application

Cooling of retort pouches and packaged products after heat sterilization.

Defrosting freezers and thawing frozen foods.



Integrated spray header

Hydraulic Spray Nozzle Header

A pipe header mounted with multiple spray nozzles, tailored to meet specific requirements.

The nozzle spacing and header length can be customized based on the spray pattern, spray angle, and spray flow rate of the nozzles used.

Contact us for further details.

Cooling After Heat Treatment

Effectively cools products after heat treatment, reducing cooling time

AJP Series




- The design without a whirler allows for a large free passage diameter, making the nozzle clog-resistant.
- Features a tangential design with the spraying axis at a 90-degree angle from the nozzle inlet.

VEP Series



- Flat spray nozzles with a uniform spray distribution across the pattern area, featuring a wear-resistant ceramic orifice.



Defrosting in Freezer

Spraying warm water to reduce the time needed for defrosting or ice removal

JJXP Series




- Full cone spray nozzles with a round-shaped spray area with uniform distribution.
- A large free passage diameter minimizes clogging.

BBXP Series



- Full cone spray nozzles with a wide 120° spray angle.
- A large free passage diameter minimizes clogging.



Water Filtration and Liquid Agitation

Reuse of cleaning and circulating water and sediment agitation

Automatic self-cleaning features resolve filter maintenance issues, achieving efficient filtration for reusing cooling water and cleaning wastewater.

- The automatic strainer ARS series automatically cleans the filtration filter, lowering operational costs by reducing maintenance frequency.
- Factory wastewater cannot be discharged as it is. It is recommended to use the ARS series to filter out impurities before discharge.

Achieve uniform liquid concentration and temperature with submerged agitation nozzles.

- For processing seasoning liquids and in similar applications, uneven liquid concentration and temperature can be issues. The submerged agitation nozzle EJX series prevents sedimentation and ensures homogenization of the liquid.

● Application

Reuse of cleaning and circulating water, and filtration of wastewater.

Agitation of sediment. Homogenization of liquid temperature and concentration.



Auto Reverse Self-cleaning Filter

Automatic Strainer ARS Filter Series

The jet spray from the equipped nozzles automatically cleans foreign particles that accumulate through filtration.

This automatic strainer eliminates the need for manual cleaning by operators, reduces maintenance tasks and labor costs, and ensures long-term durability of its filtration performance through non-contact high-pressure cleaning with wear-resistant nozzles.

Reuse of Circulating Water

Removing foreign particles from cleaning water and cooling water for their recirculation and reuse


Automatic Strainer

ARS Filter Series




- Automatically cleans foreign particles that accumulate due to filtration and maintains its filtration performance.
- Significantly reduces maintenance costs.

Watch How the ARS Filter Works!



Unfiltered water flows from outside to inside of the filter that catches foreign particles.



ARS filter detects the pressure difference between inlet **A** and outlet **B** caused by accumulated foreign particles on the filter.



After suspending water supply, ARS starts jet spray cleaning then discharges foreign particles from the drain.



After the pre-set duration, cleaning stops, and supply of unfiltered water starts again (back to the step 1).

Liquid Agitation

Agitating the liquid to prevent sedimentation and to homogenize the liquid concentration and temperature

EJX Series





- The submerged nozzles eject 3 to 4 times the volume of supplied liquid while intaking the surrounding liquid.

Two-direction Jet

EJX-2 Series




- The submerged nozzles eject the liquid in two directions at a 45-degree angle for enhanced agitation. Contactus for details.



For Effective Use of Nozzles

Spray Nozzle Precision Guarantee


All IKEUCHI's precision-made hydraulic spray nozzles are guaranteed for spray capacity and spray angle. Additionally, the spray pattern is inspected according to our own standards, and only the nozzles that pass inspection are shipped. This precision guarantee ensures that we can provide a reliable, safe product that consistently meets all customer need.



Fog Classification System

IKEUCHI has utilized a proprietary fog classification system based on spray droplet size, as outlined below. While there are various opinions on droplet size classification, we use the system described here to provide fog solutions tailored to customer applications and operating environments. Terms such as 'Dry Fog' and 'fine fog' in our catalogs are derived from this classification.

This classification is based on the spray droplet size, by measuring the spray droplet diameter with the immersion sampling method.



Spray Nozzle Selection

When selecting a nozzle, it is important to choose one that matches your specific application in terms of material, type, and spray pattern.

Nozzle Type

Hydraulic Spray Nozzles



These nozzles spray using liquid only. With a wide variety of nozzle types available, you can select the appropriate spray pattern and spray flow rate to suit your needs.

For water savings, slurry or high-volume spraying






Pneumatic Spray Nozzles



These nozzles utilize a high-velocity flow of compressed air to produce fine spray droplets at low flow rates, allowing significant liquid savings. They have a wide free passage diameter, which helps to prevent clogging.









For great water saving, precise cleaning

Spray Pattern

Main Use for:	Powerful cleaning	Wide spray coverage		Strong, pinpoint spray	Film-like stream with no gap
Spray Pattern:	Flat Spray	Hollow Cone Spray	Full Cone Spray	Solid Stream Spray	Slit Spray
Spray pattern is defined as the horizontal cross sectional shape of the spray.					
					

Other Factors

Spray performance can be affected by a variety of factors. Choose a nozzle material suited to the operating environment and liquid properties.

With or without streaking	Spray impact	Spray droplet diameter	Wear resistance	Chemical resistance	Heat resistance	Pressure resistance	Viscosity
							

For Effective Use of Nozzles

Benefits of Switching Nozzles


Effective use of nozzles can save both water and energy. Here are some effective ways to utilize them.

Eliminating Variations to Achieve Even Distribution

When using nozzles in a multi-nozzle arrangement as shown below, variations in each nozzle's performance can lead to uneven flow distribution, resulting in inconsistent cooling or incomplete cleaning, which can ultimately affect product quality.

This issue can be resolved by using our precision-guaranteed nozzles. Our spray nozzles provide reliable performance, enabling uniform cleaning that not only enhances product quality but also optimizes water usage, eliminating waste.


Comparison of Spray Distribution in Multi-nozzle Arrangements:



Use Nozzles Over Perforated Pipes

If you are using pipes with just holes instead of nozzles, you may be wasting a significant amount of water. Even for rough cleaning or simple water supply, running water through perforated pipes can consume a surprisingly large volume of water.

Using appropriate nozzles with optimal spacing can significantly enhance water-saving efficiency.



For a target width of 500 mm, with a hole diameter of 1.0 mm, hole spacing of 20 mm, and a pressure of 0.3 MPa:

Spray flow rate = **50 L/min** (2 L/min × 25 holes)


For a target width of 500 mm, using VVP nozzles with a spray angle of 90°, a spray height of 100 mm, a nozzle spacing of 150 mm, and a pressure of 0.3 MPa:

Spray flow rate = **20 L/min** (5 L/min × 4 nozzles)

This results in a **water saving of 30 L/min** compared to using a perforated pipe, leading to significant water conservation.

Selecting Optimal Spray Patterns

With the same pressure and flow rate, the spray impact increases in the following order: full cone spray pattern < flat spray pattern < solid stream spray pattern. Therefore, for applications such as conveyor cleaning where the target is moving, using a flat spray nozzle instead of a full cone nozzle allows you to achieve the same spray impact with less water.




Switching Nozzle Types

If your site has access to compressed air, you might consider changing the type of nozzle to achieve greater water-saving efficiency. For example, switching from hydraulic spray nozzles to pneumatic spray nozzles has reduced water usage by up to 70% in some cases (though costs for supplied air power are required).


Hydraulic spray nozzle

Model: 1/4M VEP 8019 S303
Liquid pressure: 0.3 MPa
Spray flow rate: 1.9 L/min



Pneumatic spray nozzle

Model: 1/8 VVEA 8010 S303
Liquid pressure: 0.3 MPa
Spray flow rate: 0.6 L/min
Air consumption: 49 L/min, Normal



For Effective Use of Nozzles

Spray Nozzle Materials

The standard and optional materials available for nozzles are shown in the material section of each nozzle series, using the material codes listed below.

If you need a specific nozzle material that is not mentioned in each series page, please contact us.

Material List

Metals	[Material code Material]
	S303 Stainless steel 303
	S304 Stainless steel 304
	S316 Stainless steel 316
	S316L Stainless steel 316L
	SCS13 Die-cast stainless steel equiv. to S304
	SCS14 Die-cast stainless steel equiv. to S316
	SCS16 Die-cast stainless steel equiv. to S316L
	S420J2 Hardened stainless steel 420J2
Rubbers	B Brass C3604
	[Material code Material]
	NBR Nitrile rubber
	FKM Fluororubber
Ceramics	FEPM Tetrafluoroethylene-propylene rubber
	EPDM Ethylene-propylene rubber
	CERJET® Ceramics
Ceramics	Alumina ceramics (Alumina 92%, etc.)
	[Material code Material]
	SiC Silicon nitride bonded silicon carbide
	SiSiC Sintered reaction-bonded silicon carbide

Plastics	[Material code Material]
	PP Polypropylene
	PPS Polyphenylene sulfide
	PVC Polyvinyl chloride
	HTPVC Heat-treated polyvinyl chloride
	PTFE Polytetrafluoroethylene
	PCTFE Polychlorotrifluoroethylene
	PVDF Polyvinylidene fluoride
	FRPP Glass-fiber reinforced polypropylene
	PA Polyamide
	PE Polyethylene
	Ultrahigh molecular weight polyethylene (UHMWPE)
	Polyester elastomer
	Araldite®*1 Epoxy resin (Adhesive)
	Araldite®H High-temperature epoxy resin (Adhesive)

*1) Araldite is the registered trademark of Huntsman Advanced Materials.

Oil-free options are available at additional cost.
Contact us for details.

Table of Chemical and Heat Resistance

Items		Chemical resistance												Heat resistance*2	
		Hydrochloric acid	Concentrated Hydrochloric acid	Sulfuric acid (35%)	Concentrated sulfuric acid	Nitric acid (35%)	Concentrated nitric acid	Acetic acid	Sodium hydroxide (caustic soda)	Aqueous ammonia	Acetone	Trichloro-ethylene	Ethyl alcohol	Suitable (°C)	Short-term use only (°C)
Metals	S303	×	×	×	×	○	△	△	○	○	○	○	○	400	800
	S304	×	×	×	×	○	○	○	○	○	○	○	○	400	800
	S316, S316L	×	×	×	○	○	△	○	○	○	○	○	○	400	800
	B	×	×	×	×	×	×	×	△	△	○	○	○	200	400
Plastics	PP	○	△	○	×	×	×	○	○	○	○	△	○	80	90
	PPS	○	○	○	△	△	×	○	○	○	○	○	○	170	180
	PVC	○	○	○	○	○	×	○	○	○	×	×	○	40	50
	HTPVC	○	○	○	○	○	×	○	○	○	×	×	○	50	70
	PTFE	○	○	○	○	○	○	○	○	○	○	○	○	100	150
	PVDF	○	○	○	○	○	○	○	△	○	×	○	○	80	120
	FRPP	○	△	○	×	×	×	○	△	○	○	△	○	90	100
	PA	×	×	×	×	△	△	△	○	○	○	○	△	130	230
	UHMWPE	○	○	○	×	△	×	○	○	○	△	△	○	80	100
	Polyester elastomer	×	×	×	×	×	×	○	△	×	△	△	○	100	120
Rubbers	Araldite®	△	×	△	×	×	×	×	×	×	×	×	×	60	70
	Araldite®H	○	×	○	△	×	×	○	△	○	○	○	○	120	140
	NBR	×	×	×	×	×	×	○	○	○	×	△	○	90	120
	FKM	○	○	○	○	○	○	○	△	×	×	○	○	150	200
Ceramics*3	FEPM	○	○	○	○	○	○	○	○	×	×	○	○	150	200
	EPDM	○	△	○	△	×	×	○	○	○	○	×	○	90	120
	CERJET® ceramics	○	○	○	○	○	○	○	×	○	○	○	○	700	800
	Alumina ceramics	○	○	○	○	○	○	○	△	○	○	○	○	1,000	1,200
Ceramics	SiC	○	○	○	○	○	○	○	△	○	○	○	○	1,550	1,550
	SiSiC	○	○	○	○	○	○	○	△	○	○	○	○	1,350	1,350

*2) The heat resistance (operating temperature limit) of spray nozzles varies widely depending on the operating conditions, environment, liquid sprayed, etc.

*3) Ceramic should be used at temperatures under 100°C to avoid a crack caused by heat shock.

Note: As for the spray nozzles including adhesive, please also take into account the heat/chemical resistance of the adhesive.

○ ... Suitable
△ ... Possible for short term
× ... Unusable



“The Fog Engineers”
H. IKEUCHI & CO., LTD.



ISO9001: 2015 certified
(H. IKEUCHI & CO., LTD., Japan only)

Global Network



Headquarters

Daiichi kyogyo Bldg., 1-15-15, Awaza, Nishi-ku, Osaka 550-0011, Japan

Tel: 81-6-6538-4015 Fax: 81-6-6538-4022

Email: overseas@kirinoikeuchi.co.jp

URL: <https://www.dry-fog.com/en/>

Overseas network

IKEUCHI USA, INC.

4722 Ritter Avenue, Blue Ash, OH 45242, USA

Tel: 1-513-942-3060

sales@ikeuchi.us

<https://www.ikeuchi.us/>

PT. IKEUCHI INDONESIA

Ruko Rodeo Drive, Jl. Hollywood Boulevard Blok B6 No. 18 & 19,
Jababeka, Bekasi, Jawa Barat 17530 Indonesia

Tel: 62-21-8938-4201 (or 4202)

sales@ikeuchi.id

<https://www.ikeuchi.id/>

IKEUCHI (SHANGHAI) CO., LTD.

Room C, 21F, Electrical & Mechanical Bldg.,
600 Hengfeng Road, Shanghai 200070, P.R.China

Tel: 86-21-6140-9731

mist@kirinoikeuchi.com

<http://www.kirinoikeuchi.com/>

Tianjin Branch Tel: 86-22-2320-1676

Shenzhen Branch Tel: 86-755-8525-2221

Wuhan Branch Tel: 86-27-8558-8299

IKEUCHI EUROPE B.V.

Merwedeweg 6, 3621 LR, Breukelen, The Netherlands

Tel: 31-20-820-2175

info@ikeuchi.eu

<https://www.ikeuchi.eu/>

SIAM IKEUCHI CO., LTD.

909 Ample Tower Bldg. 8FL., Unit 8/2, 8/3, Debaratana Road,
Bangna Nuea, Bangna, Bangkok 10260 Thailand

Tel: 66-2-348-3801 Fax: 66-2-348-3802

thai@ikeuchi.co.th

<https://www.ikeuchi.co.th/>

IKEUCHI TAIWAN CO., LTD.

11F-1, No.27, Sec.1, Chung Shan N. Road, Taipei 10441,
Taiwan, R.O.C.

Tel: 886-2-2511-6289 Fax: 886-2-2541-6392

sales@ikeuchi.com.tw

<http://www.ikeuchi.com.tw/>